

The Redundancy of a Computable Code on a Noncomputable Distribution

Łukasz Dębowski

Centrum Wiskunde & Informatica
 Science Park 123, NL-1098 XG Amsterdam
 The Netherlands
 Email: debowski@cwi.nl

Abstract—We introduce new definitions of universal and superuniversal computable codes, which are based on a code’s ability to approximate Kolmogorov complexity within the prescribed margin for all individual sequences from a given set. Such sets of sequences may be singled out almost surely with respect to certain probability measures.

Consider a measure parameterized with a real parameter and put an arbitrary prior on the parameter. The Bayesian measure is the expectation of the parameterized measure with respect to the prior. It appears that a modified Shannon-Fano code for any computable Bayesian measure, which we call the Bayesian code, is superuniversal on a set of parameterized measure-almost all sequences for prior-almost every parameter.

According to this result, in the typical setting of mathematical statistics no computable code enjoys redundancy which is ultimately much less than that of the Bayesian code. Thus we introduce another characteristic of computable codes: The catch-up time is the length of data for which the code length drops below the Kolmogorov complexity plus the prescribed margin. Some codes may have smaller catch-up times than Bayesian codes.

I. WHAT IS A GOOD COMPUTABLE CODE?

Giving a reasonable definition to the notion of a good general-purpose compression algorithm is very important. Not so much for the practical data compression but rather for a theoretical analysis of statistical inference and machine learning. All parameter estimation or prediction algorithms can be transformed into compression algorithms via the idea of the plug-in code [1], [2], see also [3, Section 6.4.3]. A transformation in the opposite direction can be done for prediction, with a guaranteed standard risk in the iid case [3, Proposition 15.1–2]. With certain restrictions, the better we compress the better we predict.

This article proposes a new simple theoretical framework for computable universal compression of random data (and thus for their prediction). Our results lie between the idealized algorithmic statistics [4], [5] and the present MDL perspective on mainstream statistical inference [6], [3], [7]. We offer a clearer path to understanding what good compression procedures are when the predicted data are generated by very complicated probability measures, cf. [8].

The prefix Kolmogorov complexity $K(x)$ is the length of a code for a string x which we can never beat more than by a constant when we use computable prefix codes [9, Chapter

3].¹ Consequently, our theoretical evaluation of compression algorithms will be based on Kolmogorov redundancy $|C(x)| - K(x)$ rather than on the traditional Shannon redundancy

$$|C(x)| + \log P(x), \quad (1)$$

where C is the inspected computable prefix code and $P \in \mathcal{M}$ is one of many candidate distributions for the data.

A large body of literature has been devoted to studying codes that are minimax optimal with respect to (1), exactly [10], [11], [12] or asymptotically [6], [3]. Let us notice that if the minimax expected Shannon redundancy

$$\min_C \sup_{P \in \mathcal{M}} \mathbf{E}_{x \sim P} [|C(x)| + \log P(x)] \quad (2)$$

or the minimax regret

$$\min_C \sup_{P \in \mathcal{M}} \max_x [|C(x)| + \log P(x)] \quad (3)$$

are finite, plausibly bounded in terms of the data length, and achieved by a unique code C then the corresponding minimax properties appear a plausible rationale to argue for code C ’s optimality against data typical of a class of distributions \mathcal{M} .

Things change when (2) or (3) are infinite since then every code is a minimizer. Infinite or unbounded minimax values appear in fact in many statistical models: (i) There are no universal redundancy rates for stationary ergodic processes [13]. (ii) Even in the parametric iid case, like Poisson or geometric, one often has to restrict the parameter range to a compact subset to have a reasonable minimax code [3, Theorem 7.1 and Sections 11.1.1–2]. In a surprising contrast, the redundancy for computable parameters can be very small, which is known as superefficient estimation/compression [14], [15], [16].

The minimax values (2) or (3) may be infinite because there is no worst case of data rather than no intuitively good code. Often there exists an intuitively good code but to single it out with the minimax criterion, we have to modify the

¹To fix our notation, the prefix code $C : \mathbb{X}^+ \rightarrow \mathbb{Y}^+$ encodes strings over a countable alphabet \mathbb{X} as strings over a finite alphabet $\mathbb{Y} = \{0, 1, \dots, D-1\}$ and \log is the logarithm to the base D . The prefix Kolmogorov complexity is considered with respect to the computer which accepts programs only from a prefix-free subset of \mathbb{Y}^+ , $\sum_x D^{-K(x)} < \Omega < 1$. We call code C computable if both C and the inverse mapping C^{-1} can be computed by the computer. $|C(x)|$ is the length of $C(x)$.

score (1) with some penalty. This idea has emerged in the MDL statistics in recent years. Grünwald [3, Sections 11.3 and 11.4] reviewed a bunch of proposed heuristic penalties, which he called the “luckiness functions” or conditional NML (normalized maximum likelihood). In general, the penalties have form $\ell(P, x)$ so the minimaximized function is

$$|C(x)| + \log P(x) - \ell(P, x) \quad (4)$$

Now, an important simple new idea. Typically for mathematical statistics, P is noncomputable (in the absolute sense). For instance, it may be given by an analytic formula with an algorithmically random parameter, to be estimated from the observed data x rather than known beforehand. On the other hand, the code C that we are searching for must be computable. We owe this insight to Vovk [17], who writes:

The purpose of estimators is to be used for computing estimates, and so their computability is essential. Accordingly, in our discussion we restrict ourselves to computable estimators.

A parameter point is not meant to be computed by anybody. Depending on which school of statistics we listen to, it is either a constant chosen by Nature or a mathematical fiction.

Consequently, the baseline $-\log P(x)$ in the coding game (1) should be replaced by *something* uniformly closer to the smallest code length that we can achieve by effective computation. The prefix Kolmogorov complexity $K(x)$ seems a fortunate candidate since

$$|C(x)| \geq K(x) - \tilde{K}(C^{-1}), \quad (5)$$

where $\tilde{K}(C^{-1})$ is the length of any program to decode C , i.e., to compute C^{-1} . When designing a general-purpose compressors C , one usually wants to keep $\tilde{K}(C^{-1})$ small.

We should subtract the generic luckiness function

$$\ell(P, x) := K(x) + \log P(x) \quad (6)$$

from the criterion (1) before the minimax is applied since otherwise we punish an intuitively good code C for unlearnable idiosyncrasies and nonuniformity of the data. The luckiness (6) does not depend on code C and its expectation is nonnegative. As we will elaborate in Section II, this very $\ell(P, x)$ is close in several senses to *algorithmic information* $I(P : x)$ about x in P .

We conjecture that $I(P : x)$ can grow for noncomputable P very fast in terms of the data length $|x|$, like any function $o(|x|)$ even in the iid case, cf. [8]. The order of the growth depends not only on the “parametric class” of P that statisticians like to think of but also on the exact “displacement” of algorithmic randomness in the possibly infinite definition of P . For instance, if P is computable given a computable parameter value then $I(P : x)$ is bounded by the finite Kolmogorov complexity of P in view of the symmetry of algorithmic information [9, Theorem 3.9.1]. This bound can be also associated with the existence of a computable superefficient estimator of the parameter [16], [15], [17].

Although $K(x)$ is noncomputable and we cannot evaluate the value of $K(x)$ for any particular string x , we can obtain sufficiently good estimates of Kolmogorov complexity for strings typical of certain probability measures. This observation inspires our new individualistic definitions of universal and superuniversal codes, which avoid minimax whatsoever. In the following, italic $x, y, \dots \in \mathbb{X}^+$ are strings (of finite length), boldface $\mathbf{x}, \mathbf{y}, \dots \in \mathbb{X}^\infty$ are infinite sequences, and calligraphic $\mathcal{X}, \mathcal{S}, \dots \subset \mathbb{X}^\infty$ are subsets of these sequences. Symbol x_n denotes the n -th symbol of \mathbf{x} and x^n is the prefix of \mathbf{x} of length n : $\mathbf{x} = x_1x_2x_3\dots$, $x^n = x_1x_2\dots x_n$. Consequently:

Definition 1.1 (universal codes): Code C is called $(\mathcal{X}, o(f(n)))$ -universal if it is a computable prefix code and $\lim_{n \rightarrow \infty} [|C(x^n)| - K(x^n)] / f(n) = 0$ holds for all $\mathbf{x} \in \mathcal{X}$.

Definition 1.2 (superuniversal codes): Code C is called $(\mathcal{X}, f(n))$ -superuniversal if it is a computable prefix code and $|C(x^n)| - K(x^n) < f(n)$ holds n -ultimately for all $\mathbf{x} \in \mathcal{X}$. Phrase “ n -ultimately” is an abbreviation of “for all but finitely many $n \in \mathbb{N}$ ”.

Although Definitions 1.1–1.2 reinterpret several probabilistic concepts of code universality that have been contemplated by Grünwald [3, pages 183, 186, and 200], only two specific kinds of known codes fall under these definitions.

The codes discovered firstly are $(\mathcal{S}, o(n))$ -universal codes for sequences typical of certain stationary measures, such as the LZ code and many similar [18], [19], [8], [20]. Namely, for each stationary probability measure \mathbf{P} over a finite alphabet there exists a set $\mathcal{S}_{\mathbf{P}}$ of infinite sequences such that $\mathbf{P}(\mathcal{S}_{\mathbf{P}}) = 1$ and LZ is $(\mathcal{S}_{\mathbf{P}}, o(n))$ -universal.² Consequently, we may put $\mathcal{S} = \bigcup_{\mathbf{P} \in \mathbb{S}} \mathcal{S}_{\mathbf{P}}$, where \mathbb{S} is the set of all such measures.

There exists also a second kind of good codes which consists of superuniversal codes for sequences typical of computable measures. For each computable measure \mathbf{P} there exists a specific set $\mathcal{B}_{\mathbf{P}}$ of infinite sequences such that $\mathbf{P}(\mathcal{B}_{\mathbf{P}}) = 1$ and a simple modification of the computable Shannon-Fano code is $(\mathcal{B}_{\mathbf{P}}, |c(n)|+1)$ -superuniversal.³ In the case of $\mathbf{P}(x) = \int \mathbf{P}_{\theta}(x) d\pi(\theta)$, we call this code the Bayesian code with respect to $(\{\mathbf{P}_{\theta}\}, \pi, c)$.

Consider the case when \mathbf{P} is computable whereas \mathbf{P}_{θ} is not necessarily so. We will see easily in Section III that $\mathbf{P}_{\theta}(\mathcal{B}_{\mathbf{P}}) = 1 = \mathbf{P}(\mathcal{B}_{\mathbf{P}})$ for π -almost all θ . This simple

²Our notation for distributions and measures follows the distinction between strings and infinite sequences. Italic P is a distribution of countably many strings x with $P(x) \geq 0$ and $\sum_x P(x) = 1$. Boldface \mathbf{P} is also a distribution of strings x , $\mathbf{P}(x) \geq 0$, but normalized against strings of fixed length $\sum_x \mathbf{P}(x) \mathbf{1}_{\{|x|=n\}} = 1$ and satisfying the consistency condition $\sum_y \mathbf{P}(xy) \mathbf{1}_{\{|y|=n\}} = \mathbf{P}(x)$. Consequently there is a unique measure on the measurable sets of infinite sequences \mathbf{x} , also denoted as \mathbf{P} , such that $\mathbf{P}(\{x : x^n = x \text{ for } n = |x|\}) = \mathbf{P}(x)$.

³We use symbol $c : \mathbb{N} \rightarrow \mathbb{Y}^+$ to denote a computable prefix code for natural numbers, $\sum_n D^{-|c(n)|} \leq 1$. For example, $c(n)$ may be chosen as the recursive ω -representation for n [21]. Then $|c(n)| = \log^* n + 1$, where $\log^* n$ is the iterated logarithm of n to the base D . A different $c(n)$ may be convenient for a study of superefficient compression, cf. [16]. By an analogy to the distinction between P and \mathbf{P} , we propose symbol \mathbf{C} to denote a system of computable prefix codes for strings of fixed length. The corresponding Kraft inequalities are $\sum_x D^{-|\mathbf{C}(x)|} \mathbf{1}_{\{|x|=n\}} \leq 1$ versus $\sum_x D^{-|\mathbf{C}(x)|} \leq 1$. Each code of form $c(|x|)\mathbf{C}(x)$ is a prefix code for strings of any length but the converse is not true.

statement establishes in fact the ultimate near-optimality of Bayesian codes with respect to $(\{P_\theta\}, \pi, c)$ also for data typical of many simple noncomputable probability measures. The statement appears very powerful since we can let P_θ be any parameterized measures considered by statisticians for years. To mention a few examples, we may consider iid Bernoulli, Poisson or discretized long-range dependent Gaussian time series. The result also explains why the MDL statistics has so resembled Bayesian inference so far.

The motivation for Bayesian codes in the MDL statistics lies in the concept of the shortest effective description rather than in beliefs. Thus, in the MDL paradigm we can go farther and ask what computable codes are significantly shorter than a fixed Bayesian code.⁴ Because of the $K(n)$ -high oscillations of Kolmogorov complexity [9, Sections 2.5.1 and 3.4], one may hardly expect that there exist $(\mathcal{X}, f(n))$ -superuniversal codes for $f(n) = o(K(n)) + O(1)$.

The ultimate redundancy does not seem a performance score that can be improved on if we can only define a computable Bayesian code for the contemplated statistical problem. This notwithstanding, another performance score can be attacked.

Definition 1.3 (catch-up time): The catch-up time for an $(\mathcal{X}, f(n))$ -superuniversal code C is the function $\text{CUT}(\cdot; C) : \mathbb{X}^\infty \rightarrow \mathbb{N} \cup \{\infty\}$ defined as

$$\text{CUT}(x; C) := \sup \{n \in \mathbb{N} : |C(x^n)| - K(x^n) \geq f(n)\}.$$

The catch-up time is the minimal length of data for which the code becomes almost as good as the Kolmogorov complexity. A simple lower bound for the catch-up time can be obtained by comparing two computable codes experimentally. Basing on the data provided by [7], we conjecture that some codes have much smaller catch-up times than Bayesian codes.

In the remaining part of this article, we detail the mentioned results. In Section II, we argue that the generic luckiness function is close to algorithmic information. In Section III, we prove that Bayesian codes are superuniversal for data typical of almost all parameter values. Some ideas for future research are sketched in the concluding Section IV.

Our framework differs in several points to what has been done in the algorithmic and MDL statistics. Firstly, we insist on computable codes but apply both Kolmogorov complexity and noncomputable probability measures to evaluate the quality of the code. Secondly, we apply a stronger version of Barron's "no hypercompression" inequality to upper bound the code length in question with the Kolmogorov complexity rather. Secondly, we apply a stronger version of Barron's "no hypercompression" inequality to upper bound the code length in question with the Kolmogorov complexity. So far Barron's inequality was only used to lower bound the code length with minus log-likelihood.

⁴We consider here only computable Bayesian inference. It has been known that $K(x)$ equals the length of certain noncomputable code having a Bayesian interpretation [9, Example 4.3.3 and Theorem 4.3.3].

II. A GENERIC "LUCKINESS" FUNCTION

We will argue in this section that the generic luckiness function $\ell(P, x) := K(x) + \log P(x)$ is close to the algorithmic information about x in P . First of all, let us recall necessary concepts:

- (i) The universal computer is a finite state machine that interacts with one or more infinite tapes on which only a finite number of distinct symbols may be written in each cell. For convenience, we allow three tapes: tape α on which a finite program is written down, tape β (oracle) on which an infinite amount of additional information can be provided before the computations are commenced, and tape γ from which the output of computations is read once they are finished. We assume that programs which the computer accepts on tape α form a prefix-free set of strings.
- (ii) To compute strings over an alphabet that is larger (e.g. countably infinite) than the alphabet allowed on tape γ , we assume that the contents of γ is sent to a fixed decoder once the computations are finished.
- (iii) The prefix Kolmogorov complexity $K(x)$ of a string x is the length of the shortest program on tape α to generate the representation of string x on tape γ when the computer does not read from tape β .
- (iv) The conditional prefix Kolmogorov complexity $K(x|y)$ is the length of the shortest program on tape α to generate the representation of string x on tape γ when the representation of object y is given on tape β .
- (v) The representation of an arbitrary distribution P on tape β is a list of probabilities $\lfloor P(x)D^m \rfloor D^{-m}$ discretized up to m digits, enumerated for all strings x and all precision levels d . (The same applies to a measure \mathbf{P} respectively.)
- (vi) If the function $(x, d) \mapsto \lfloor P(x)D^m \rfloor D^{-m}$ can be computed by a program then we put $K(P)$ to be the length of the shortest such program and call P computable. If P is not computable, we let $K(P) := \infty$.

The old idea of Shannon-Fano coding [22, Section 5.9] yields thus the following proposition:

Theorem 2.1: [5, the proof of Lemma II.6] For a computer-dependent constant A ,

$$K(x|P) + \log P(x) \leq A, \quad (7)$$

$$\mathbf{E}_{x \sim P} [K(x|P) + \log P(x)] \geq 0. \quad (8)$$

Constant A is the length of any program on tape α which computes x given the mapping $y \mapsto P(y)$ put on tape β and x 's Shannon-Fano codeword of length $\lceil -\log P(x) \rceil$ appended on tape α after the program. Inequality (8) is the noiseless coding theorem for entropy and an arbitrary prefix code.

The version of (7) for measure \mathbf{P} requires an additional term to identify the string length. Now constant A becomes the length of a program on tape α which computes x given the mapping $y \mapsto \mathbf{P}(y)$ put on tape β , the prefix-free representation of the string length $n = |x|$ appended on tape α after the program, and x 's Shannon-Fano codeword of length

$\lceil -\log \mathbf{P}(x) \rceil$ appended on tape α after that. As the prefix-free representation of n , we choose the shortest program to generate n . The length of this program is denoted as $K(n)$. For any computable code c for natural numbers, we have also

$$K(n) \leq \tilde{K}(c^{-1}) + |c(n)|,$$

where $\tilde{K}(c^{-1})$ is the length of any program to decode c .

Theorem 2.2: For a computer-dependent constant A ,

$$K(x^n | \mathbf{P}) + \log \mathbf{P}(x^n) \leq A + K(n), \quad (9)$$

$$\mathbf{E}_{\mathbf{x} \sim \mathbf{P}} [K(x^n | \mathbf{P}) + \log \mathbf{P}(x^n)] \geq 0. \quad (10)$$

Moreover,

$$K(x^n | \mathbf{P}) + \log \mathbf{P}(x^n) > 0 \quad (11)$$

n -ultimately for \mathbf{P} -almost all sequences \mathbf{x} .

Inequality (11) stems from a bit stronger version of Barron's inequality than given in [23, Theorem 3.1]:

Lemma 2.3 (Barron's "no hypercompression" inequality):

Let W be a prefix code for strings of any length, not necessarily computable. Then

$$|W(x^n)| + \log \mathbf{P}(x^n) > 0 \quad (12)$$

n -ultimately for \mathbf{P} -almost all sequences \mathbf{x} .

Remark: We may put $|W(x)| := K(x|\text{anything fixed})$ or $|W(x)| := K(m) + K(x|f(m))$, where m depends on x in whatever way.

Proof: Consider function $Q(x) = D^{-|W(x)|}$. By the Markov inequality,

$$\begin{aligned} \mathbf{P}((12) \text{ is false}) &= \mathbf{P}\left(\frac{Q(x^n)}{\mathbf{P}(x^n)} \geq 1\right) \\ &\leq \mathbf{E}_{\mathbf{x} \sim \mathbf{P}} \left[\frac{Q(x^n)}{\mathbf{P}(x^n)} \right] = \sum_x \mathbf{1}_{\{|x|=n\}} Q(x). \end{aligned}$$

Hence $\sum_n \mathbf{P}((12) \text{ is false}) \leq \sum_x D^{-|W(x)|} \leq 1 < \infty$ by the Kraft inequality. In the following, we derive the claim with the Borel-Cantelli lemma. ■

Let us recall that the algorithmic information about x in \mathbf{P} is

$$I(\mathbf{P} : x) := K(x) - K(x|\mathbf{P}) \geq 0 \quad (13)$$

[9, Definition 3.9.1]—the last inequality holds without any additive constant for our definition of universal computer. A bit different definition of symmetric algorithmic information $I(x; y)$ is sometimes also convenient [5, Eq. II.3]. As a corollary of Theorems 2.1 and 2.2, we obtain bounds for luckiness term (6) which read

$$\begin{aligned} \ell(\mathbf{P}, x) - I(\mathbf{P} : x) &\leq A, \\ \mathbf{E}_{\mathbf{x} \sim \mathbf{P}} [\ell(\mathbf{P}, x) - I(\mathbf{P} : x)] &\geq 0, \\ \ell(\mathbf{P}, x^n) - I(\mathbf{P} : x^n) &\leq A + K(n), \\ \mathbf{E}_{\mathbf{x} \sim \mathbf{P}} [\ell(\mathbf{P}, x^n) - I(\mathbf{P} : x^n)] &\geq 0, \end{aligned}$$

whereas $\ell(\mathbf{P}, x^n) - I(\mathbf{P} : x^n) > 0$ n -ultimately for \mathbf{P} -almost all sequences \mathbf{x} .

III. BAYES IS OPTIMAL FOR ALMOST ALL PARAMETERS

Adjust the programs for computing x from its Shannon-Fano codeword so that they use a built-in subroutine for computing $x \mapsto P(x)$ written on tape α rather than read the definition of this mapping from tape β . Then we have:

Theorem 3.1: [9, Theorem 8.1.1] For a computer-dependent constant A ,

$$K(x) + \log P(x) \leq A + K(P), \quad (14)$$

$$\mathbf{E}_{\mathbf{x} \sim \mathbf{P}} [K(x) + \log P(x)] \geq 0. \quad (15)$$

Theorem 3.2: For a computer-dependent constant A ,

$$K(x^n) + \log \mathbf{P}(x^n) \leq A + K(\mathbf{P}) + K(n), \quad (16)$$

$$\mathbf{E}_{\mathbf{x} \sim \mathbf{P}} [K(x^n) + \log \mathbf{P}(x^n)] \geq 0. \quad (17)$$

Moreover,

$$K(x^n) + \log \mathbf{P}(x^n) > 0 \quad (18)$$

n -ultimately for \mathbf{P} -almost all sequences \mathbf{x} .

There are several simple corollaries of Theorem 3.2.

Definition 3.3 (Barron random sequence): A sequence \mathbf{x} will be called \mathbf{P} -Barron random if (18) holds n -ultimately for \mathbf{x} . The set of such sequences will be denoted as $\mathcal{B}_{\mathbf{P}}$.

Definition 3.4 (Bayesian code): The Bayesian code with respect to $(\{\mathbf{P}_{\theta}\}, \pi, c)$ is the mapping $C : \mathbb{X}^+ \ni x \mapsto C(x) = c(|x|)C(x) \in \mathbb{Y}^+$, where $c : \mathbb{N} \rightarrow \mathbb{Y}^+$ is a code for natural numbers, $C(x)$ is the Shannon-Fano codeword for x with respect to $\mathbf{P}(x) = \int \mathbf{P}_{\theta}(x) d\pi(\theta)$, $\{\mathbf{P}_{\theta} : \theta \in \Theta\}$ is a family of probability measures, and π is a prior probability.

Corollary 3.5: If the measure \mathbf{P} and code $c : \mathbb{N} \rightarrow \mathbb{Y}^+$ are computable then the Bayesian code with respect to $(\{\mathbf{P}_{\theta}\}, \pi, c)$ is $(\mathcal{B}_{\mathbf{P}}, |c(n)| + 1)$ -superuniversal.

Proof: Of course, the hypothesis implies that C is a computable prefix code. We have $|C(x)| = |c(|x|)| + \lceil -\log \mathbf{P}(x) \rceil$. If (18) holds then $|C(x^n)| - K(x^n) < |c(n)| + 1$. So C is $(\mathcal{X}, |c(n)| + 1)$ -superuniversal. ■

Barron randomness is a refinement of a better known concept of algorithmic randomness of sequences. Let us recall that sequence \mathbf{x} is \mathbf{P} -Martin-Löf random if and only if

$$K(x^n) + \log \mathbf{P}(x^n) \geq -c \quad (19)$$

for some $c \geq 0$ and all n [9, Definition 2.5.4 and Theorem 3.6.1]. Denote the set of these sequences as $\mathcal{L}_{\mathbf{P}}$. We have $\mathcal{L}_{\mathbf{P}} \supset \mathcal{B}_{\mathbf{P}}$ so $\mathbf{P}(\mathcal{L}_{\mathbf{P}}) = \mathbf{P}(\mathcal{B}_{\mathbf{P}}) = 1$. If $\mathbf{x} \in \mathcal{L}_{\mathbf{P}} \setminus \mathcal{B}_{\mathbf{P}}$, however, the catch-up time $\text{CUT}(\mathbf{x}; C)$ is infinite for $|C(x)| = |c(|x|)| + \lceil -\log \mathbf{P}(x) \rceil$.

In the next step we will interpret the set of Barron random sequences $\mathcal{B}_{\mathbf{P}}$ as a superset of sequences typical of certain not necessarily computable measures \mathbf{P}_{θ} .

Corollary 3.6: Consider a probability measure of form $\mathbf{P}(x) = \int \mathbf{P}_{\theta}(x) d\pi(\theta)$ for any measurable parameterization $\Theta \ni \theta \mapsto \mathbf{P}_{\theta}$ where both prior π and \mathbf{P}_{θ} are probability measures. Equality $\mathbf{P}_{\theta}(\mathcal{B}_{\mathbf{P}}) = 1$ holds for π -almost all θ .

Proof: Let $\mathcal{G}_n := \{\theta \in \Theta : \mathbf{P}_{\theta}(\mathcal{B}_{\mathbf{P}}) \geq 1 - 1/n\}$. By Theorem 3.2, $1 = \mathbf{P}(\mathcal{B}_{\mathbf{P}}) \leq \pi(\mathcal{G}_n) + \pi(\Theta \setminus \mathcal{G}_n)(1 - 1/n) = 1 - n^{-1}\pi(\Theta \setminus \mathcal{G}_n)$. Thus $\pi(\mathcal{G}_n) = 1$. Finally, we appeal to

σ -additivity of π . For $\mathcal{G} := \{\theta \in \Theta : P_\theta(\mathcal{B}_P) = 1\} = \bigcap_n \mathcal{G}_n$ we obtain $\pi(\mathcal{G}) = \inf_n \pi(\mathcal{G}_n) = 1$. ■

Corollaries 3.5 and 3.6 demonstrate that the *ultimate* redundancy of a Bayesian code is nearly optimal when compared with any computable code on data typical of noncomputable parameterized measures P_θ . This statement holds for any imaginable statistical model $\{P_\theta : \theta \in \Theta\}$. Computability of the Bayesian code is the only restriction and the only caveat is that $P_\theta(\mathcal{B}_P) = 1$ holds for prior-almost all parameters $\theta \in \Theta$ rather than for all of them.

Example 3.7 (a code for “almost all” distributions): This example stems from the observation that we can encode any probability measure on \mathbb{X}^∞ with a single infinite sequence $\theta = \theta_1\theta_2\theta_3\dots$ over the alphabet $\mathbb{Y} = \{0, 1, \dots, D-1\} \ni \theta_n$.⁵

For simplicity let the input alphabet be the set of natural numbers, $\mathbb{X} := \mathbb{N}$. The link between θ and a measure P_θ will be established by imposing equality $P_\theta(x^n) =$

$$\left(P_\theta(x^{n-1}) - \sum_{y \in \mathbb{N}: y < x_n} P_\theta(x^{n-1}y) \right) \cdot \sum_{k=1}^{\infty} \theta_{\phi(x^n, k)} D^{-k}, \quad (20)$$

where $P(\lambda) = 1$ for the empty word and a bijection $\phi : \mathbb{N}^+ \times \mathbb{N} \rightarrow \mathbb{N}$ is used. It is easy to see that P_θ is a probability measure on \mathbb{X}^∞ for each θ . Conversely, each probability measure on \mathbb{X}^∞ equals P_θ for at least one θ .

Let the prior be the uniform iid measure $\pi(\theta^m) := D^{-m}$ for $\theta^m := \theta_1\theta_2\dots\theta_m$. The Bayesian measure $P(x) = \int P_\theta(x) d\pi(\theta)$ is computable. Consequently, the Bayesian code with respect to $(\{P_\theta\}, \pi, c)$ is computable and $(\mathcal{B}_P, |c(n)| + 1)$ -superuniversal.

Whereas parameterization (20) is general, the measure P introduced in this example equals simply $\log_2 P(x^n) = -\sum_{i=1}^n x_i$. Although $P_\theta(\mathcal{B}_P) = 1$ for π -almost all θ , the Bayesian code with respect to this P is suboptimal for stationary measures different to P .

IV. CONCLUSION

We hope that our simple insights may be used in future research to better characterize several paradoxical phenomena that have haunted the emerging MDL statistics. These phenomena are: nonexistence of universal redundancy rates, superefficient compression/estimation, converging and diverging Bayesian predictors, and various “catch-up” phenomena.

It is important to understand for which particular parameters the claim of Corollary 3.6 holds or fails. Inspired by [17] and [4], we have started contemplating the following problem:

Question 4.1: Consider a computable measure $P(x) = \int P_\theta(x) d\pi(\theta)$, where parameter values θ are infinite sequences as well. Let \mathcal{X} be the set of sequences for which the Bayesian code with respect to $(\{P_\theta\}, \pi, c)$ is $(\mathcal{X}, |c(n)| + \mathcal{E}(n))$ -universal. What does $P_\theta(\mathcal{X})$ equal for θ that (i) are algorithmically random, or (ii) exhibit a deficiency of algorithmic randomness (e.g. they are computable)?

⁵One can also put $\theta = \sum_{k=1}^{\infty} \theta_k D^{-k}$ since the set of real numbers having two different D -ary expansions is negligible.

We have already proved that $P_\theta(\mathcal{X}) = 1$ for (i) whereas $P_\theta(\mathcal{X}) = 0$ for (ii) under some natural conditions, e.g., for exponential iid distributions P_θ .

The second group of interesting open problems concerns catch-up times. Can we know the catch-up times approximately? How can we use this knowledge to verify or to falsify a statistical model for concrete data of limited length?

V. ACKNOWLEDGEMENT

We express our thanks to Peter Grünwald for interesting and enjoyable discussions which stimulated us to write this paper. The research reported in this work was supported in part by the IST Program of the European Community, under the PASCAL II Network of Excellence, IST-2002-506778, and done on the author’s leave from the Institute of Computer Science, Polish Academy of Sciences.

REFERENCES

- [1] A. Dawid, “Present position and potential developments: Some personal views, statistical theory, the prequential approach,” *J. Roy. Statist. Soc. A*, vol. 147, pp. 278–292, 1984.
- [2] J. Rissanen, “Universal coding, information, prediction, and estimation,” *IEEE Trans. Inform. Theor.*, vol. 30, pp. 629–636, 1984.
- [3] P. D. Grünwald, *The Minimum Description Length Principle*. The MIT Press, 2007.
- [4] P. Vitányi and M. Li, “Minimum description length induction, Bayesianism and Kolmogorov complexity,” *IEEE Trans. Inform. Theor.*, vol. 46, pp. 446–464, 2000.
- [5] P. Gács, J. Tromp, and P. M. B. Vitányi, “Algorithmic statistics,” *IEEE Trans. Inform. Theor.*, vol. 47, pp. 2443–2463, 2001.
- [6] A. Barron, J. Rissanen, and B. Yu, “The minimum description length principle in coding and modeling,” *IEEE Trans. Inform. Theor.*, vol. 44, pp. 2743–2760, 1998.
- [7] T. van Erven, P. Grünwald, and S. de Rooij, “Catching up faster by switching sooner: A prequential solution to the AIC-BIC dilemma,” 2008, <http://arxiv.org/abs/0807.1005>.
- [8] Ł. Dębowski, “On the vocabulary of grammar-based codes and the logical consistency of texts,” 2008, e-print: <http://arxiv.org/abs/0810.3125>. Submitted to IEEE Transactions on Information Theory. In open review.
- [9] M. Li and P. M. B. Vitányi, *An Introduction to Kolmogorov Complexity and Its Applications, 2nd ed.* Springer, 1997.
- [10] F. Topsøe, “Information theoretical optimization techniques,” *Kybernetika*, vol. 15, pp. 8–27, 1979.
- [11] Y. M. Shtarkov, “Universal sequential coding of single messages,” *Probl. Inform. Transm.*, vol. 23(2), pp. 3–17, 1987.
- [12] D. Haussler, “A general minimax result for relative entropy,” *IEEE Trans. Inform. Theor.*, vol. 43, pp. 1276–1280, 1997.
- [13] P. C. Shields, “Universal redundancy rates don’t exist,” *IEEE Trans. Inform. Theor.*, vol. IT-39, pp. 520–524, 1993.
- [14] L. Le Cam, “On sets of parameter points where it is possible to achieve superefficiency of estimates,” *Ann. Math. Statist.*, vol. 23, p. 148, 1953.
- [15] V. Vovk, “Asymptotic efficiency of estimators: an algorithmic approach,” *Theor. Probab. Appl.*, vol. 36, pp. 329–343, 1991.
- [16] A. Barron and N. Hengartner, “Information theory and superefficiency,” *Ann. Statist.*, vol. 26, pp. 1800–1825, 1998.
- [17] V. Vovk, “Superefficiency from the vantage point of computability,” 2009, submitted to the Statistical Science.
- [18] J. Ziv and A. Lempel, “A universal algorithm for sequential data compression,” *IEEE Trans. Inform. Theor.*, vol. 23, pp. 337–343, 1977.
- [19] D. Neuhoff and P. C. Shields, “Simplicistic universal coding,” *IEEE Trans. Inform. Theor.*, vol. IT-44, pp. 778–781, 1998.
- [20] J. Kieffer, “A unified approach to weak universal source coding,” *IEEE Trans. Inform. Theor.*, vol. 24, pp. 674–682, 1978.
- [21] P. Elias, “Universal codeword sets and representations for the integers,” *IEEE Trans. Inform. Theor.*, vol. 21, pp. 194–203, 1975.
- [22] T. M. Cover and J. A. Thomas, *Elements of Information Theory*. Wiley, 1991.
- [23] A. R. Barron, “Logically smooth density estimation,” Ph.D. dissertation, Stanford University, 1985.